


Theory and Analysis of MEMS Resonators



V. Kaa'akar
Chief Scientist, MEMS Resonators

Why MEMS? Batch fabrication of microresonators with IC-like processing and methods


one 200 mm wafer
> 50 000 chips!



Vito Kaa'akar
2011 IEEE Inertial and Frequency Control of Symposium



Mechanical resonators and filters



Mechanical filter example:
455 kHz AM band pass filter

- Low frequency mechanical filters ubiquitous between 40's and 80's. Bulky and costly by today's standards. Low frequency filter market dominated by ceramic and IC filters.
- High frequency mechanical filters still irreplaceable. Example: SAW band pass filters.
- As are quartz resonators used for oscillators.


Vito Kaa'akar
2011 IEEE Inertial and Frequency Control of Symposium



Why micromechanical resonators?

- small size
- power consumption
- integrability

- what IC cannot do:
 - stability
 - small dissipations (high-Q)




=> compact,
high-performance
devices!

Vito Kaa'akar
2011 IEEE Inertial and Frequency Control of Symposium




Resonance frequency of tuning fork



Vito Kaa'akar
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators




First MEMS resonator: Resonating gold MOS gate in 60's!


Vito Kaa'akar
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators



Microguitar (1997)



Improved microguitar (2003)
- you can actually play it
(with a laser beam)

Mike Kozlowski
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators

Flexural polysilicon resonator




Fig. 2: SEM of an 8.5 MHz clamped-clamped beam μ mechanical resonator with a typical measured spectrum [15].

C. T.-C. Nguyen et al., University of Michigan

Mike Kozlowski
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators

Contour mode polysilicon resonators




Fig. 4: SEM of a fabricated 156 MHz contour-mode disk μ mechanical resonator with a measured frequency characteristic [20].


C. T.-C. Nguyen et al., University of Michigan

Mike Kozlowski
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators

Square extensional plate resonator



- First MEMS resonator to meet GSM specifications for noise (signal to noise ratio 150 dB!)
- Narrow electrode gaps needed to reduce the bias voltage ($d = 200 \text{ nm}$ and $V_{\text{bias}} = 20 \text{ V}$ gives $R_m = 600 \Omega$)


P. Rantakari, et al., "Low noise, low power micromechanical oscillator," in Transducers'05, Seoul, Korea, 5-9 Jun. 2005, pp. 2135- 2138.

Mike Kozlowski
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators

Square extensional plate resonator




- First MEMS resonator to meet GSM specifications for noise (signal to noise ratio 150 dB!)
- Narrow electrode gaps needed to reduce the bias voltage ($d = 200 \text{ nm}$ and $V_{\text{bias}} = 20 \text{ V}$ gives $R_m = 600 \Omega$)

P. Rantakari, et al., "Low noise, low power micromechanical oscillator," in Transducers'05, Seoul, Korea, 5-9 Jun. 2005, pp. 2135- 2138.

Mike Kozlowski
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators



- First commercially available MEMS timing product from start-up SiTime
- $R_m = 1 \text{ M}\Omega$ at $V = 4.6$. Differential measurement needed!
- The temperature drift and fabrication offsets are compensated with a phase locked loop (not shown).



Photo of MEMS die





Die bonded to an IC

Mike Kozlowski
2011 IEEE Inertial and Frequency Control of Symposium



Examples of microresonators




R. Ruby, *et al.* (Agilent Technologies), ISSCC 2001.

- Film Bulk Acoustic Resonator (FBAR)
- Used commercially in cell phones (filters, duplexers)

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control Symposium




This course



Microguitar

VS.



FBAR

What separates commercial success from "mere" technology demonstrations?

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control Symposium



Outline

- Part 1: modeling of microresonators
 - Lumped models for distributed resonator
 - Electrostatic and piezoelectric actuation
- Part 2: figures of merit
 - Quality factor
 - Electromechanical coupling coefficient
- Part 3: Oscillator applications
- Part 4: Filter applications
- LOTTERY!

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control Symposium



Modeling challenge

Vibrations of, for example, guitar string:




Which part is mass and which spring?

- Resonators usually have distributed mass and elasticity.
- Analyzing distributed resonators requires solving 3D stress fields either analytically or with finite element analysis (FEM).
- For system analysis, lumped mass-spring model or electrical equivalent model are preferred.

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control Symposium



Resonator example:
Electrostatically actuated BAW resonator




Ends extending and contracting (length extensional mode)
Mattila *et al.*, 2002

$f_r = 13 \text{ MHz}$
 $Q > 100,000$

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control Symposium



Resonator example:
Electrostatically actuated BAW resonator




Longitudinal mode beam resonator [Mattila02]. A distributed system.

➡ How to represent with a lumped mass spring model?

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control Symposium




Distributed BAW resonator vibrations



Wito Krasner
2011 IEEE In ems and P. Frequency Cont. of Symposium



Lumped model for forced vibrations



Wito Krasner
2011 IEEE In ems and P. Frequency Cont. of Symposium



Lumped model for forced vibrations (continued)

$$\rho A \frac{\partial^2 x}{\partial t^2} \sin \frac{\pi z}{L} + bA \frac{\partial x}{\partial t} \sin \frac{\pi z}{L} + EA \left(\frac{\pi}{L}\right)^2 x \sin \frac{\pi z}{L} = 0$$

Multiply by mode shape $u = \sin \frac{\pi z}{L}$ and integrate over the beam length to give

$$\underbrace{\frac{\rho A L}{2}}_m \frac{\partial^2 x}{\partial t^2} + \underbrace{\frac{b A L}{2}}_\gamma \frac{\partial x}{\partial t} + \underbrace{\frac{E A \pi^2}{2 L}}_k x = 0$$

$$m \frac{\partial^2 x}{\partial t^2} + \gamma \frac{\partial x}{\partial t} + kx = 0$$

Compare to the geometrical mass and dc-spring:


$$m = \rho A L$$

$$k = E \frac{A}{L}$$

Wito Krasner
2011 IEEE In ems and P. Frequency Cont. of Symposium



Lumped model for forced vibrations (continued)



- Lumped harmonic resonator can be used to model the vibration mode in distributed resonator.
- Distributed system has infinite number of resonances. Additional resonances can be modeled by having several harmonic resonators in parallel. Often one resonance is all that is needed.

Wito Krasner
2011 IEEE In ems and P. Frequency Cont. of Symposium



Practical analysis

- Often mode shape and resonance frequency are known
 - FEM
 - Vibration encyclopedia (e.g. Roark's)
- Integrate mode shape to get the effective mass

$$m = \int \rho U^2 dV$$

mode shape


$$k = \omega_0^2 m$$

Wito Krasner
2011 IEEE In ems and P. Frequency Cont. of Symposium




Example: clamped-clamped beam

Clamped-clamped resonator:



Mode shape:



Mode shape:

$$U_1(X) = C_1 [\sinh \beta_1 X/L - \sin \beta_1 X/L + \alpha_1 (\cosh \beta_1 X/L - \cos \beta_1 X/L)]$$

Effective mass:

$$m = \int \rho U^2 dV = \rho A \int_0^L U_1^2(X) dX = 0.40 \rho A L \approx 8.8 \text{ pkg}$$

Resonance frequency:

$$\omega_0 = \frac{\beta_1}{\sqrt{12}} \sqrt{\frac{E}{\rho}} \frac{\pi}{L^2}$$

Effective spring:

$$k = \omega_0^2 m \approx 819 \text{ N/m}$$

Wito Krasner
2011 IEEE In ems and P. Frequency Cont. of Symposium



Recap

- Resonators have distributed mass and spring
- The vibration mode can be modeled with effective mass and spring => lumped mechanical model
- Next step: electrical equivalent

Milo Kozlowski
2011 IEEE Inertial and Frequency Control Symposium




Why electrical equivalents

- Analytical work is simplified if all effects of physics, mechanics, and circuits are in the same domain.
- Circuit simulators are powerful and very robust
=> Filter and quartz oscillator design work is done with circuit simulators
- Philosophical: it is good to start with a simple physics based model and add complexity if necessary. (Compare to starting with complex finite element simulation).

Milo Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Step #1: Electrical equivalent circuits



Milo Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Step #2: Electromechanical coupling

- Electromechanical coupling needed to:
 - convert excitation **voltage into force**
 - convert mechanical **displacement into signal current**
 - Several transduction methods are possible:
 - Capacitive transduction.
 - Based on electrostatic force and conservation of charge.
 - Well suited for micromachining.
 - Widely used in MEMS gyroscopes and accelerometers.
 - Piezoelectric transduction.
 - Used in >99.9% of all commercial devices (quartz resonators, SAW and FBAR filters).
 - Material property. Unfortunately silicon is not piezoelectric.
 - Magnetic transduction.
 - Piezoresistive sensing.
 - Thermal actuation.
- Not used commercial devices and therefore not covered here.

Milo Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Capacitive transduction - force

$$F = \frac{\partial W}{\partial x} = \frac{\partial}{\partial x} \left(\frac{1}{2} C v^2 \right)$$

$$\approx \frac{1}{2} v^2 \frac{C_0}{d} = \frac{C_0}{2d} (v_{dc}^2 + 2V_{dc}v_{ac} + v_{ac}^2)$$

dc-force ac-force assumed small

$$C = \epsilon \frac{A}{d-x}$$

$$C_0 = \epsilon \frac{A}{d}$$

Force at excitation frequency:
 $F = \eta v_{ac}$ where $\eta = V_{dc} \frac{C_0}{d}$

Milo Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Capacitive transduction - current

$$i = \frac{\partial C v}{\partial t} = v \frac{\partial C}{\partial t} + C \frac{\partial v}{\partial t}$$

$$\approx V_{dc} \frac{\partial C}{\partial t} + C_0 \frac{\partial v_{ac}}{\partial t}$$

$$V_{dc} \frac{\partial C}{\partial t} = V_{dc} \frac{\partial C}{\partial x} \frac{\partial x}{\partial t} \approx \eta \frac{\partial x}{\partial t}$$

motional current "normal" current

$$i \approx \eta \frac{\partial x}{\partial t} + C_0 \frac{\partial v_{ac}}{\partial t} = \eta \frac{\partial x}{\partial t} + j\omega C_0 v_{ac}$$

Milo Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Practical realization

dc bias resistor (blocks ac)

ac by bass capacitor

Voltage here: $V_{dc} + v_{ac}$

$C = \epsilon \frac{A_d}{d - x}$

VTI TECHNOLOGIES

Transformer model for coupling

$F = \eta v_{ac}$

$i = i_{mot} + i_{ac}$

$\approx \eta \ddot{x} + j\omega C_0 v_{ac}$

VTI TECHNOLOGIES

MEMS resonator model

Lumped model

Electrical equivalent

$F = \eta v_{ac}$

$v = \frac{i}{\eta}$

VTI TECHNOLOGIES

Comparison of simulation and experiment

Measurement and electrical equivalent model agree very well!

VTI TECHNOLOGIES

Putting it all together: MEMS resonator model

Physical system

Electrical equivalents

$F = \eta v_{ac}$

$i_{mot} = \eta v$

VTI TECHNOLOGIES

Typical values for the beam BAW

Mechanical parameters:			
Spring constant	K	22	MN/m
Effective mass	M	340	pkg
Quality factor	Q	100 000	

Electrical parameters ($U_{dc} = 100$ V, $d = 1$ μm):			
Motional capacitance	C_m	0.35	aF
Motional inductance	L_m	430	H
Motional resistance	R_m	350	kΩ

Electrical parameters ($U_{dc} = 10$ V, $d = 0.1$ μm):			
Motional capacitance	C_m	35	aF
Motional inductance	L_m	4.3	H
Motional resistance	R_m	900	Ω

➡ Motional impedance is a strong function of gap (and bias)

VTI TECHNOLOGIES


Recap

- Equations for mechanical resonator can be represented with a LRC-circuit
- Electrostatic coupling is based on variable capacitor
 - Electrostatic force and current through the capacitor depend on the electromechanical transduction factor η
- Next step: nonlinear effects

Vito Kozdziej
2011 IEEE Int. Symp. on Freq. Contr. & Symp.



Nonlinear effects: Amplitude limit due to nonlinear springs



- Can be of capacitive or mechanical origin (fundamentally limited by material nonlinearity)
- Bifurcation (hysteresis) at large vibration amplitudes.
- Sets limit to resonator power handling capacity!

V. Kaajakari et al, IEEE J. MEMS

Vito Kozdziej
2011 IEEE Int. Symp. on Freq. Contr. & Symp.



Nonlinear effects: Capacitive nonlinear springs

Taylor series expansion of the force:

$$F = \frac{\partial W}{\partial x} = \frac{\partial}{\partial x} \left(\frac{1}{2} C(x) V_d^2 \right)$$

$$C = \epsilon \frac{A}{d-x} = \frac{C_0}{2d} V_d^2 \left(1 + \frac{2x}{d} + \frac{3x^2}{d^2} + \frac{4x^3}{d^3} + \dots \right)$$


$F \sim x$, linear spring
Can be used to adjust frequency!

Nonlinear springs!

Vito Kozdziej
2011 IEEE Int. Symp. on Freq. Contr. & Symp.



Nonlinear effects: Power handling capacity



Nonlinear forced excitations:

$$m \frac{\partial^2 x}{\partial t^2} + \gamma \frac{\partial x}{\partial t} + k_0(1 + k_1 x + k_2 x^2)x = f(t)$$

Critical vibration amplitude: $x_c = \frac{2}{\sqrt{3Q|k|}}$, $\kappa = \frac{3}{8}k_2 - \frac{5}{12}k_1^2$

Maximum energy stored in resonator: $E_{\max} = \frac{1}{2}k_0 x_c^2$

Resonator power handling capacity: $P_{\max} = \frac{E_{\max} \omega_0}{Q}$

Signal to noise ratio $\sim \frac{E_{\max}}{k_B T}$ (remember that thermal noise is $k_B T$)

V. Kaajakari et al, IEEE J. MEMS

Vito Kozdziej
2011 IEEE Int. Symp. on Freq. Contr. & Symp.



Nonlinearity: implications

- The signal is reduced with shrinking size
 - Bulk resonators typically have larger signal than microresonators
 - Nanomechanical is worse than micromechanical!
 - Signal-to-noise ratio (S/N) decreases with size
- Non-linear effects should be minimized for large S/N
 - Stiff structures (bulk, not flexural)
 - Linear coupling (piezoelectric, not electrostatic)
- Meeting phase noise specifications with microresonators is a challenge
- Microresonators may not be suitable for filters
 - Large interfering signal will mix and alias to signal band

Vito Kozdziej
2011 IEEE Int. Symp. on Freq. Contr. & Symp.



Recap of nonlinearity

- The maximum signal level easy to evaluate if nonlinear spring constants are known
 - Trivial with capacitive coupling
 - Mechanical nonlinearity harder to model
- Fundamental challenge to miniaturization!
- Next: **piezoelectric transduction**

Vito Kozdziej
2011 IEEE Int. Symp. on Freq. Contr. & Symp.



Piezoelectric resonators

Quartz crystal

Grind-polish-metal deposition

Final package

Fundamental Mode Thickness Shear

- No bias voltage needed
- Strong electromechanical coupling
- Simple and cheap

VTI TECHNOLOGIES

Modeling piezoelectric coupling

Metal electrodes

$$T = YS - eE$$

$$T = YS$$

Force model

$$F = e_{33}A_3E_3$$

$$F = e_{33}A_3E_3$$

Constitutive model

- Stress is sum of mechanical and piezoelectric strain
- Coupled mechanical and electrical equations
- A lot of bookkeeping!

Lumped model

- Piezoelectric stress due to a lumped force at the location of electrodes
- Piezoelectric material modeled as a regular solid

VTI TECHNOLOGIES

Transduction factor for piezoelectric resonators

3

1

$T = YS - eE$

$$\eta_{eff} = 2 \frac{e_{33}A}{h}$$

$$F = \eta_{eff} v_{ac}$$

$$i = \eta_{eff} \dot{x} = j\omega_0 \eta_{eff} x$$

- Distributed vibrations can be modeled with a lumped mass and spring (as with capacitive MEMS)
- The electromechanical coupling can be modeled with effective electromechanical transduction factor (as with capacitive MEMS)

VTI TECHNOLOGIES

Example: FBAR

Electrodes

Piezoelectric thin film (AlN)

$$m = \frac{\rho AL}{2}$$

$$k = \frac{EA\pi^2}{2L}$$

$$\eta_{eff} = 2 \frac{e_{33}A}{h}$$

Simplest model:

- 1D vibrations in the thickness mode only
- Compare to 1D BAW we already analyzed
- Caveat: real resonators have multiple "spurious modes"

VTI TECHNOLOGIES

Example: FBAR at 900 MHz

Electrodes

Piezoelectric thin film (AlN)

$$\rho = 3200 \text{ kg/m}^3$$

$$A = (500 \text{ } \mu\text{m})^2$$

$$h = 6 \text{ } \mu\text{m}$$

$$e_{33} = 1.55 \text{ C/m}^2$$

$$m = \frac{\rho AL}{2} = 2.4 \text{ nkg}$$

$$k = \frac{EA\pi^2}{2h} = 82.2 \text{ GN/m}$$

$$\eta_{eff} = 2 \frac{e_{33}A}{h} = 0.1292 \text{ N/V}$$

VTI TECHNOLOGIES

Example: FBAR at 900 MHz continued

Electrodes

Piezoelectric thin film (AlN)

$$C_0 = \epsilon_R \epsilon_0 \frac{A}{h} = 3.1 \text{ pF}$$

$$R_m = \frac{\sqrt{km}}{Q\eta^2} = 0.8 \text{ } \Omega$$

$$C_m = \frac{\eta^2}{k} = 200 \text{ fF}$$

VTI TECHNOLOGIES


Recap of piezoelectric transduction

- Piezoelectric resonators can be modeled as lumped systems
 - Analysis identical to lumped models for electrostatic resonators
- The effective electromechanical transduction depends on the location of the electrodes and material constants
- Next: **Transducer location dependency**

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Location of transducer matters




Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Lumped force

The effective force is also normalized by the mode shape.



Effective force counting the both forces and mode shape:


$$F_{eff} = F \sin \beta Z_1 - F \sin \beta (-Z_1) = 2F \sin \beta Z_1$$

Effective transduction factor: $\eta_{eff} = \eta_0 2 \sin \beta Z_1$

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Lame resonator example



X-displacement:
 $U_x = \sin \frac{\pi X}{L} \cos \frac{\pi Y}{L}$
 Y-displacement:
 $U_y = -\sin \frac{\pi X}{L} \cos \frac{\pi Y}{L}$

Effective transduction factor for electrode 1:

$$U_x \left(X = \frac{L}{2} \right) = \cos \frac{\pi Y}{L}$$

$$\eta_{eff} = \eta_0 \int_{-L/2}^{L/2} \cos \frac{\pi Y}{L} dY = \frac{\eta_0}{2}$$

where

$$\eta_0 = e_{31} \frac{A}{d^2} V_{dc}$$

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Recap of transducer location dependency

- The transduction factor is normalized by the resonator mode shape.
 - For maximum coupling, electrodes should be placed at the location of maximum vibration amplitude
- Next: **Part 2: figures of merit**

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Outline

- Part 1: modeling of microresonators
 - Lumped models for distributed resonator
 - Electrostatic vs. piezoelectric actuation
- Part 2: figures of merit**
 - Quality factor
 - Electromechanical coupling coefficient
- Part 3: Oscillator applications
- Part 4: Filter applications

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium




Definitions for quality factor


(1) Physical definition

$$Q = 2\pi \frac{\text{Energy stored}}{\text{Energy dissipated per cycle}}$$

(2) Transmission peak width




(3) Slope of transmission phase



Vito Kozlovski
2011 IEEE Inertial and Frequency Control of Symposium



Importance of quality factor in oscillators



- Low noise: resonator is effective narrow bandwidth filter
- Stability of the oscillator: small changes in circuit do not change oscillation frequency


Leeson's formula for phase noise:

$$L \propto \frac{k_B T}{2P} \left[1 + \left(\frac{\omega_0}{2Q\Delta\omega} \right)^2 \right]$$

Vito Kozlovski
2011 IEEE Inertial and Frequency Control of Symposium



Importance of quality factor in oscillators



- Low noise: resonator is effective narrow bandwidth filter
- Stability of the oscillator: small changes in circuit do not change oscillation frequency

Example:

$$Q = 100,000$$

$$d\Phi = 5^\circ = 0.087 \text{ rad}$$

$$\frac{d\omega}{\omega_0} = \frac{d\Phi}{2Q} = 0.4 \text{ ppm}$$

Vito Kozlovski
2011 IEEE Inertial and Frequency Control of Symposium




Loss effects in microresonators

- Gas damping
 - Dominant loss mechanism unless vacuum packaging is used
 - Very high quality vacuum needed to minimize losses
- Anchor losses
 - Resonator vibrations couple to substrate/packaging
 - Significant especially for low frequency resonators
- Intrinsic losses
 - Material dependent viscous losses
 - Low for hard, crystalline materials (quartz, silicon...)

Vito Kozlovski
2011 IEEE Inertial and Frequency Control of Symposium




Gas damping



Vito Kozlovski
2011 IEEE Inertial and Frequency Control of Symposium




Minimizing anchor losses



Vito Kozlovski
2011 IEEE Inertial and Frequency Control of Symposium



Scaling law for intrinsic losses



- Anchor losses dominate in flexural resonators
- Intrinsic losses limit bulk mode resonators
- f-Q-product approximately constant for given material

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Recap of quality factor

- Characterizes losses in resonator
 - Material losses
 - Anchor losses
 - Gas damping
- Important for oscillator signal quality and stability
- Important for filter performance
- Next: **Electromechanical coupling coefficient k_{eff}^2**

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium




Electromechanical coupling coefficient

- Electromechanical coupling coefficient is defined as

$$k_{eff}^2 = \frac{\text{energy converted}}{\text{input energy}}$$

- For example, electrostatic resonator vibrating between two extremes x_1 and x_2 trades mechanical energy to electrical energy




Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Electromechanical coupling coefficient

$$k_{eff}^2 = \frac{\eta^2}{kC_0} = \frac{C_m}{C_0}$$



Series resonance:

$$\omega_0 = \frac{1}{\sqrt{C_m L_m}}$$

Parallel resonance (anti-resonance):

$$\omega_A = \omega_0 \sqrt{1 + \frac{C_m}{C_0}} = \omega_0 \sqrt{1 + k_{eff}^2}$$


Note:

$$k_{eff}^2 = \frac{\omega_A^2 - \omega_0^2}{\omega_A^2} \approx 2 \frac{\omega_A - \omega_0}{\omega_0}$$

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Electromechanical coupling coefficient



Coupling coefficient:

- ⇒ Strength of coupling relative to mechanical stiffness
- ⇒ Measures distance between resonance and anti-resonance.
- ⇒ Tuning range for capacitive loaded oscillators
- ⇒ Bandwidth for ladder filters


$$k_{eff}^2 = \frac{\omega_A^2 - \omega_0^2}{\omega_A^2} \approx 2 \frac{\omega_A - \omega_0}{\omega_0}$$

$$k_{eff}^2 = \frac{\eta^2}{kC_0} = \frac{C_m}{C_0}$$

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Electromechanical coupling coefficient



Coupling coefficient:

- ⇒ Strength of electromechanical coupling relative to mechanical stiffness
- ⇒ Measures distance between resonance and anti-resonance.
- ⇒ Tuning range for capacitive loaded oscillators
- ⇒ Bandwidth for ladder filters
- ⇒ Insertion loss for filters

$$k_{eff}^2 = \frac{\omega_A^2 - \omega_0^2}{\omega_A^2} \approx 2 \frac{\omega_A - \omega_0}{\omega_0}$$

$$k_{eff}^2 = \frac{\eta^2}{kC_0} = \frac{C_m}{C_0}$$

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Combining Q and k_{eff}^2

- Product of Q and k_{eff}^2 is a figure of merit for resonators:

$$Qk_{\text{eff}}^2 = \frac{1}{\omega_0 C_m R_m} \frac{C_0}{C_0} = \frac{1}{\omega_0 C_0 R_m}$$

- Importance easy to understand by noting that $Z_0 = \frac{1}{\omega_0 C_0}$ is the characteristic impedance in filter design:

$$Qk_{\text{eff}}^2 = \frac{1}{\omega_0 C_0 R_m} = \frac{Z_0}{R_m}$$

- In resonators, tells how much signal goes through motional resonators vs C0

Mike Kaprielian
2011 IEEE Inertial and Frequency Control Symposium



Recap of electromechanical coupling coefficient

- Characterizes strength of coupling
- Depends on
 - stiffness (energy stored in spring)
 - capacitance (electrical energy stored)
 - transduction factor (energy converted)
- Important for oscillator signal magnitude
- Important for filter performance
- Next: **Part 3: Oscillator applications**

Mike Kaprielian
2011 IEEE Inertial and Frequency Control Symposium



Outline

- Part 1: modeling of microresonators
 - Lumped models for distributed resonator
 - Electrostatic vs. piezoelectric actuation
- Part 2: figures of merit
 - Quality factor
 - Electromechanical coupling coefficient
- Part 3: Oscillator applications**
- Part 4: Filter applications

Mike Kaprielian
2011 IEEE Inertial and Frequency Control Symposium



Reference oscillators


- Radio communication, high speed data transfer
- High frequency, typically 26 MHz
- Low power consumption needed, typically 1 mA
- Moderate to high accuracy, typically +/- 20 ppm over consumer temperature band

Mike Kaprielian
2011 IEEE Inertial and Frequency Control Symposium



Quartz resonator

Quartz crystal oscillator (10-40 MHz)




- advantages: well understood, low cost (<0.5 EUR), temperature stable to 1 ppm, long term stable to 0.1 ppm/year
- disadvantage: significant space consumer on circuit board!

Mike Kaprielian
2011 IEEE Inertial and Frequency Control Symposium




Size disadvantage illustration “Single-chip” Bluetooth radio



Mike Kaprielian
2011 IEEE Inertial and Frequency Control Symposium




MEMS approach Integrated reference and IC



Vito Kasper
2011 IEEE In emss - oral F. frequency Cont. of Symposium



Why a frequency reference?




Vito Kasper
2011 IEEE In emss - oral F. frequency Cont. of Symposium



Why a frequency reference?

- To establish communication!
 - a fundamental need for wireless devices
 - especially important for portable devices
 - the more accurate the reference - the less scanning required (quick link start-up)
 - high-Q => low noise




Vito Kasper
2011 IEEE In emss - oral F. frequency Cont. of Symposium



Silicon microresonators - suitable for reference oscillator application?

Critical issues to achieve in micro-size:


- Long-term stability
 - material stability
 - surface stability
- Noise performance
 - spectral purification in transceivers (sensitivity and selectivity)



Vito Kasper
2011 IEEE In emss - oral F. frequency Cont. of Symposium



Long-term stability of silicon microresonators (material stability)




Diamond lattice => very stable material, suitable for reference application.

Vito Kasper
2011 IEEE In emss - oral F. frequency Cont. of Symposium









Wafer level vacuum encapsulation




Vito Kasper
2011 IEEE In emss - oral F. frequency Cont. of Symposium






MEMS vs. quartz noise performance



V. Kaajakari et al, IEEE J. MEMS
2011 IEEE Int. Symp. on Freq. Contr. and Symp.

VTI TECHNOLOGIES

Demonstrator: Prototype resonator and off-the-self electronics




V. Kaajakari et al, IEEE J. MEMS
2011 IEEE Int. Symp. on Freq. Contr. and Symp.

VTI TECHNOLOGIES

Silicon *micro*resonators - suitable for reference oscillator application?

Critical issues to achieve in micro-size:

- (1) Long-term stability
 - ✓ - material stability
 - surface stability
- (2) Noise performance
 - ✓ - spectral purification in transceivers (sensitivity and selectivity)



V. Kaajakari et al, IEEE J. MEMS
2011 IEEE Int. Symp. on Freq. Contr. and Symp.

VTI TECHNOLOGIES


Recap of stability and noise performance

- Microresonators susceptible to drift
 - Large surface to volume area
 - Careful packaging and good design needed to meet aging specifications (drift < 1ppm/year)
- Demonstrated quality factors compatible to bulk resonators
- Silicon BAW based oscillators can have phase noise comparable to quartz
- Next: the "accuracy problem"

V. Kaajakari et al, IEEE J. MEMS
2011 IEEE Int. Symp. on Freq. Contr. and Symp.

VTI TECHNOLOGIES

Accuracy challenge #1: silicon temperature dependency




Silicon Young's modulus changes about -60 ppm/K.
In comparison: quartz resonator can be more than 100x better.

V. Kaajakari et al, IEEE J. MEMS
2011 IEEE Int. Symp. on Freq. Contr. and Symp.

VTI TECHNOLOGIES

TCXO

- TCXO = temperature compensated crystal oscillator
- Temperature measured and oscillator actively tuned with a series capacitor to cancel temperature dependency
- Temperature dependency ~1 ppm from -45 to 85 °C!



$$\omega_{mc} = \omega_0 \sqrt{1 + \frac{C_m}{C_0 + C_p/2}}$$

range: $\omega_0 < \omega_{mc} < \omega_A$

$$k_{off}^2 = \frac{\eta^2}{k C_0} = \frac{C_m}{C_0}$$

$$\omega_A = \omega_0 \left(1 + \frac{k_{off}^2}{2} \right)$$

Maximum tuning range depends on electromechanical coupling coefficient!

V. Kaajakari et al, IEEE J. MEMS
2011 IEEE Int. Symp. on Freq. Contr. and Symp.

VTI TECHNOLOGIES

Quartz TCXO


- Uncompensated temperature drift ~ 20 ppm
 - Coupling coefficient $k_{eff}^2 \sim 1800$ ppm
 - Maximum tuning range ~900 ppm
- This is more than sufficient!

$$k_{eff}^2 = \frac{C_m}{C_0}$$

CX95M AT CRYSTAL
14 MHz to 250 MHz
Low Profile, Ultra-Miniature
Surface Mount AT Quartz Crystal




EQUIVALENT CIRCUIT



Vito Kozubler
2011 IEEE Inertial and P. Frequency Control Symposium



SiTime oscillator



$$\eta = 7 \cdot 10^{-7} \text{ N/V}$$

$$k = 250 \text{ kN/m}$$

$$C_0 = 0.1 \text{ pF}$$


$$k_{eff}^2 = \frac{\eta^2}{k C_0} = 20 \text{ ppm}$$

Vito Kozubler
2011 IEEE Inertial and P. Frequency Control Symposium



Silicon TCXO

- Uncompensated temperature drift ~ 3000 ppm
 - Coupling coefficient $k_{eff}^2 \sim 20$ ppm
 - Maximum tuning range ~ 10 ppm
- This is far from sufficient!
- Solution: compensate temperature digitally outside the oscillator loop with a phase locked loop




Vito Kozubler
2011 IEEE Inertial and P. Frequency Control Symposium




Silicon vs. quartz resonators

QUARTZ OSCILLATOR:



COMPENSATED MEMS OSCILLATOR:
Compensation adds noise (jitter) + consumes power




- MHz MEMS makes sense if fractional-N PLL is already in the system.
- Standalone MEMS oscillators have few advantages over quartz oscillators (smaller size and better shock performance).

Vito Kozubler
2011 IEEE Inertial and P. Frequency Control Symposium



Recent research: Temp. compensation of silicon by doping



TEMPERATURE COMPENSATED SINGLE-DEVICE ELECTROMECHANICAL OSCILLATORS
Arash Hajim, Amir Rattahouz, and Sivasankar Pournazeri
MEMS2011

- Phosphorus doped resonators show reduced temperature dependency
- How sensitive the temperature dependency is to doping variations?

Vito Kozubler
2011 IEEE Inertial and P. Frequency Control Symposium



Accuracy challenge #2: Manufacturing variations

- Typical manufacturing variations in lithography and DRIE processing $> \pm 100$ nm
 - Flexural resonators with 3 μ m spring width have $3/2 \pm 100/3000 = \pm 50,000$ ppm frequency variations
 - BAW resonators ($L = 300$ nm) have $\Delta L/L = \pm 0.1/300 = \pm 300$ ppm frequency variations
- Quartz resonators are trimmed to have initial accuracy better than ± 50 ppm (typically ± 20 ppm)
- MEMS manufacturing variations have to be compensated
 - physical trimming (difficult with wafer level processes especially after wafer level packaging)
 - electronic trimming (same PLL as used for temperature compensation)

Vito Kozubler
2011 IEEE Inertial and P. Frequency Control Symposium



Real time clocks (RTCs)

- A real-time clock (RTC) is a computer clock (most often in the form of an integrated circuit) that keeps track of the current time. Although the term often refers to the devices in personal computers, servers and embedded systems, RTCs are present in almost any electronic device which needs to keep accurate time.

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control of Symposium



Case for MEMS in RTC

- Noise/jitter is not a major concern
=> Low signal level not a major concern
- Good electromechanical coupling at low frequencies
=> Easy to make a good oscillator
- Plenty of experience in kHz resonators (gyroscopes!)
=> Manufacturing processes readily available.
- kHz quartz is difficult to miniaturize
=> A real advantage over the incumbent

$$f_0 = \frac{1}{2\pi} \sqrt{\frac{k}{m}}$$


$$k_{eff}^2 = \frac{\eta^2}{\rho C_0}$$

Can be ~10,000x smaller at kHz compared to MHz

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control of Symposium



MEMS RTC architecture



- Low power MEMS oscillator core
- Temperature sensor to compensate the MEMS drift
- Temperature dependent counter to obtain 1 Hz pulses

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control of Symposium



First MEMS based RTC

±5ppm, I²C Real-Time Clock

General Description

The DS3231M is a low-cost, extremely accurate, I²C real-time clock (RTC). The device incorporates a battery input and maintains accurate timekeeping when main power to the device is interrupted. The integration of the microelectromechanical system (MEMS) resonator enhances the long-term accuracy of the device and packages the piece-part count in a manufacturing line. The DS3231M is available in the same footprint as the popular DS3231 RTC.

The RTC maintains seconds, minutes, hours, day, date, month, and year information. The date at the end of the month is automatically adjusted for months with fewer than 31 days, including corrections for leap year. The clock operates in either the 24-hour or 12-hour format with an AM/PM indicator. Two programmable time-of-day alarms and a 1Hz output are provided. Address and data are transferred serially through an I²C bidirectional bus. A precision temperature-compensated voltage reference and comparator circuit monitors the status of V_{CC} to detect power failures, to provide a reset output, and to automatically switch to the backup supply when power is lost.

Features

- Timekeeping Accuracy ±5ppm (±0.432 Second/Day) from -40°C to +85°C
- Battery Backup for Continuous Timekeeping
- Low Power Consumption
- Footprint and Functionality Compatible to DS3231
- Complete Clock Calendar Functionality Including Seconds, Minutes, Hours, Day, Date, Month, and Year with Leap Year Compensation Up to Year 2100
- Two Time-of-Day Alarms
 - 1Hz and 32.768kHz Outputs
- Reset Output and Pushbutton Input with Debounce
- Fast (100kHz) I²C-Compatible Serial Bus
- ±2.5V to ±5.5V Supply Voltage
- Digital Temp Sensor with ±3°C Accuracy
- 40°C to +85°C Temperature Range
- 16-Pin SO (306 mils) Package

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control of Symposium



Recap of time references

- Quartz is a special material:
 - temperature dependency is almost zero
 - the remaining small dependency can be compensated by tuning the resonator. Good coupling makes this easy.
- Silicon has a **HUGE** temperature dependency
 - Meeting even XO performance requires complex compensation circuitry
 - Promising research on doping
 - Compensation of manufacturing variations at wafer level requires innovation
- MEMS is well suited for RTC applications
- Next: **Part 4: Filter applications**

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control of Symposium




Outline

- Part 1: modeling of microresonators
 - Lumped models for distributed resonator
 - Electrostatic vs. piezoelectric actuation
- Part 2: figures of merit
 - Quality factor
 - Electromechanical coupling coefficient
- Part 3: Oscillator applications
- Part 4: Filter applications**

Mike Kozlowski
2011 IEEE In-ense and P. Frequency Control of Symposium















FBAR

- Film bulk acoustic resonator (FBAR).
- Also known is Bulk Acoustic Wave (BAW) resonator.
- Thin film vibrating (mainly) in thickness mode.
- Excellent performance at 1 - 6 GHz.
- Used commercially as band pass filters in cell phones.


Vito Kozlovski
2011 IEEE In-enna - oral P. frequency Cont. of Symposium

VTI
TECHNOLOGIES





Silicon GHz resonators



J. Wang, Z. Ren, and C.-C. Nguyen, "1.156-GHz self-aligned vibrating micromechanical disk resonator," IEEE Trans. Ultrason., Ferroelect., Freq. Contr., vol. 51, no. 12, pp. 1607-1628, Dec. 2004.

- Electrostatic actuation (DC bias voltage needed)
- One-to-one replacement of SAW not demonstrated
- **Frequency determined by lateral (mask) dimensions – a filter bank possible**
- Demonstrated to 1 GHz with high R_m (over 1 M Ω). This challenge is fundamental.
- Coupling coefficient is low (<0.01%). This challenge is fundamental.

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium




Recap of filter applications

- FBAR resonators have high electromechanical coupling coefficient. Needed for
 - Meeting the bandwidth requirements
 - Meeting the insertion loss requirements
- Electrostatically actuated silicon resonators at ~1 GHz have poor electromechanical coupling coefficient
 - Not suitable for current system architectures. Revolution in radio systems?
 - Piezoelectric coupling?
- Next: **Relax, we are done!**

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



Current MEMS timing market is miniscule - Future?



Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium



References

- MEMS resonator modeling:
 - Ville Kaajakari, Practical MEMS, Small Gear Publishing, 2009.
- MEMS based communications system architectures:
 - C. Nguyen, "MEMS technology for timing and frequency control," IEEE Trans. Ultrasonics, Ferroelectrics and Frequency Control, vol. 54, no. 2, pp. 251-270, Feb. 2007.
- Critical comparison of MEMS and crystal technology:
 - C. S. Lam, A Review of the recent development of MEMS and crystal oscillators and their impacts on the frequency control products industry, IEEE Ultrasonics Symposium, 2008, pp. 694-704.
- FBAR resonators:
 - J. Kallila, Review of wave propagation in BAW thin film devices, IEEE Ultrasonics Symposium, 2007, pp. 120-129.
 - R. Ruby et. al., "Thin film bulk wave acoustic resonators (FBAR) for wireless applications", IEEE Ultrasonics Symposium, 2001, pp. 813-821.

Mike Kozlowski
2011 IEEE Inertial and Frequency Control Symposium

