

# Index

- Acceleration, 34
- Aging, 14, 29, 232
- Allan Variance, 19
- Amplitude of oscillation, 4, 63
- Analogue temperature compensation, 130–146
- Antiresonant frequency, 23
- AT cut crystal, 25, 27
- Base spreading resistance, 47
- Bessel functions, 201, 224
- Bias shift, 50, 54
- Calibration tolerance, 28, 231
- Capacitance, load, 25
- Clapp oscillator, 56, 85–88, 193–194
- Collector current, 51, 54
- Collector limiting, 6
- Colpitts oscillator, 56, 76–84, 197–198, 216–223
- Compensation, temperature, 16
  - analogue, 130–146
  - digital, 131, 152–157
  - hybrid, 146–152
  - microprocessor, 157–176
- Component tolerance, 120
- Crystal
  - aging, 14, 29, 232
  - drive level, 26, 64
  - equivalent circuit, 21
  - holder, 38, 233
  - load capacitance, 25, 120, 228
  - marking, 233
  - military, 32–37
  - oven, 15, 126
  - overtone, 30
  - pin-to-pin capacitance, 25
  - Q factor, 29
  - reactance, 22, 23, 230
  - resistance, 24, 26, 35–37
  - specification, 231–234
  - temperature curves, 27, 28
  - temperature equation, 171
- CT cut crystal, 28
- Dewar flask, 127
- Diffusion capacitance, 47
- Digital temperature compensation, 131, 152–157
- Drift tolerance, 231
- Drive level, 26, 32
- DT cut crystal, 28
- Emitter resistance, 47
- Environmental effects, 14
- Equivalent circuit
  - crystal, 21, 227, 229
  - transistor, 43, 45, 48, 53
- Equivalent resistance, 231
- Experimental method of design, 4
- Finishing tolerance, 28, 231
- Frequency modulation, 17
- Frequency of oscillation, 3
- Frequency stability, 14, 16, 26, 119
- Gain, 3, 128
- Gate oscillators
  - multiple, 106–110
  - single, 100–105
- Grounded base oscillator, 7, 89–100, 188–192
- Harmonic balance, 216–223
- Harmonic current, 51–54
- Holder capacitance, 20, 25
- Holder, crystal, 38, 233
- Hybrid analogue-digital temperature compensation, 131, 146–152

- Hybrid  $\pi$  equivalent circuit, 44
- Hyperbolic Bessel functions, 49, 201, 219
- Impedance inverting Pierce oscillator, 72–76
- Impedance transformation ratio, 11
- Insulation resistance, 232
- Integrated circuit oscillator, 110–118
- Interpolation, temperature curve, 158
- Intrinsic transistor, 47
- J cut crystal, 28
- Leakage, 232
- Load capacitance, 25
- Load isolation, 141–145
- Logic gate oscillator, 100–110
- Long term stability, 14, 16
- Loop gain, 3, 6, 128
- Marking, crystal, 233
- Measurement, 231
- Memory size, 157
- Microprocessor temperature compensation, 157–176
- Military crystals, 32–38
- Multiple gate oscillators, 106–110
- Negative resistance oscillators, 113–114
- Nonlinear model, transistor, 46
- Nonlinear modifications, 11
- NT cut crystal, 28
- Oscillator
  - Clapp, 56, 85–88, 193–194
  - Colpitts, 56, 74–84, 197–198, 216–223
  - gate, 100–110
  - grounded base, 7, 89–100, 188–192
  - Pierce, 56–72, 180–187, 195–196
  - principles, 3
- Oven, crystal, 15, 126
- Overtone, crystal, 30
- Overtone Pierce oscillator, 70
- Parallel resonant frequency, 22
- Phase, in oscillator, 3
- Phase modulation, 17
- Phase stability, 17
- Pierce oscillator, 56–72, 180–187, 195–196
- Pin-to-pin capacitance, 25
- Power gain analysis, 7
- Production tests, 119
- Proportionally controlled oven, 15
- Pullable oscillator, 122
- Q factor, crystal, 29
- Quality control, 233
- Quartz crystal. *See* Crystal
- Relaxation oscillation, 127
- Resistance, 24, 26, 35–37, 231
- S parameters, 44
- Series resonant frequency, 21
- Shock, 34, 232
- Short term stability, 17
- Single gate oscillator, 100–106
- Spurious modes, 231
- Spurious response, 30, 31
- Spurious oscillation, 120, 125, 127, 128
- Squegging, 127
- Storage temperature, 232
- Switch, crystal, 121, 128
- TXCO, 130
- Temperature coefficient, crystal, 27–28, 171
- Temperature compensation
  - analogue, 130–146
  - digital, 131, 152–157
  - hybrid, 146–152
  - microprocessor, 157–176
- Temperature control, 15, 126
- Temperature effects on stability, 14
- Test drive level, crystal, 26, 231
- Testing, 119, 234
- Thermistor, 133
- Transistor, 40, 44, 47
  - equivalent circuit, 41
- Transition capacitance, 47
- Unwanted modes, 231
- VCXO, 122–126
- Vibration, 32, 232
- Voltage controlled crystal oscillator, 122–126
- Voltage regulation, 140
- XY cut crystal, 28
- Y parameter design, 5, 42, 180, 188