

Index

Where piezoelectric crystal properties are involved, quartz is understood unless otherwise mentioned.

- A**, angles for designating plate orientation, 69, 114
- Abrasives, kinds, 293
 - sizing, 294
- Acid test equipment, 535
- Acoustic effects, 286, 432
- Activity of crystals, 393-410
 - see also* Oscillator—amplitude of oscillations
- Adjusting of crystal units to frequency, 317, 434, 528
 - of GT orientation compensation, 441
 - of sealed crystal units, 432
- Aging, 321, 435, 529
- Air-filled sealed units, 432, 434
- Air-gap effect on frequency, 286, 432
- Air-gap mounting, 285
- Air transportation promoted by crystal development, 5
- Allison, S. K., 99
- Aloxite, 295
- Aluminum coatings, 340, 416
- Aluminum oxide, 294
- Alundum, 295
- American Tel. & Tel. Co., 4
- Amplitude of oscillations—*see* Oscillator—Amplitude of oscillations
- Angular orientation—*see* Cuts
- Angular orientations, locus of, for zero coefficient NT, 550
- Armstrong, E. J., 95
- Assembly, 430, 525
- Atanasoff and Hart, 42, 56
- AT cut—*see* Cuts
 - dimensioning, 246
 - interfering resonances, 234, 236
 - mode of motion, 211
- Atomic planes, distance between (d), 99, 100, 103
 - derivation of vector normal, 121
 - early hypothesis of, 99
 - intercepts on X-Y-Z derived from Miller indices, 118, 119
 - Miller indices, 101, 102, 104, 106, 107
 - Miller indices and reflection intensity, 117
 - naming of, 101
- Atomic planes, for orientation of given face, 116
 - orientation with respect to plate edges, 118-121
- Atomic planes—*Cont.*
 - parallel to the X axis, diagram, 107
 - reflect X-rays strongly, 105-107
 - zonal relations, 135, 136
- Axes, crystallographic, 101
 - relation between a-b-c and X-Y-Z, 104
 - rectangular or orthogonal, 103, 104
 - right- and left-handed systems, 103, 104, 106
 - X, Y, Z, 170
 - X, Y, Z defined, 103, 104
- Axial ratio of quartz— c/a , 103
- Bechmann, R.**, 25, 50
- Bell Telephone Laboratories, 6, 8, 427
- Bifluoride etching compounds, 192
- Birefringence, 151
- Blue inclusions, 144, 145, 159-161
- Boella, M., 380, 381
- Bond, W. L., 57, 95, 115, 170, 219, 290, 422
- Bown, R., 4
- Bozorth, R. M., 97
- Bragg angle, 99, 100, 105
- Bragg law of X-ray diffraction, 99
- Bravais-Miller indices, 101
- BT cut—*see* Cuts
 - dimensioning, 241
 - interfering resonances, 235, 238
 - mode of motion, 211
- Bubble inclusions, 144, 159, 161
- Bumpers, 429
- Bureau of Standards, 2
- Cady, W. G.**, 1, 13, 14, 20, 41, 356, 357, 358, 374
- Cages for mounting, 429
- Caldwell, W. C., 342
- Calibration, general, 318, 325
 - in factory, 528
 - PI meter, 467
- Cantilever mounting, 278
- Cap faces, indices of, 104
- Carborundum, 295
- Chaffee, E. L., 383, 405
- Channel spacings and crystal control, 7
- Characteristic radiation, 95-97
- Characteristics of oscillators by PI meter, 474
- Chemistry of etching, 190-194

- Chrome oxide, 295
 Chuva, 145
 Circle diagram for crystal, 481
 Circuits, equivalent of crystal, 21, 46, 358
 equivalent of crystal in PI meter, 459
 crystal combinations, 484
 comparator, duplicator, 327
 D spec. test set, 330
 PI meter, 463, 465
 plating machine, 352
 see Oscillator circuits also
 Citrine quartz, 143
 Clamp type mounting (center), 276, 413
 Clamp type mounting (corners), 285
 Cleaning, 435, 527
 Cleaning edges, 420, 521, 522
 Cleavage figures, 165, 189
 Coatings for plated units, 414
 Coatings—*see* Plating, etc.
 Color filters for quartz inspection, 149, 150
 Color of quartz, 141–143
 Colpitts, E. H., 360
 Cooling liquids, 297
 Combined twinning, 198
 Comparator, 327
 Comparison of various measured temperature coefficients, 55, 201
 Compliance, stiffness relation, 38
 Compton, A. H., 99
 Conductivity, electrical and thermal, 164
 Conformal representation, 479
 Conoscope, instrument, 504–505
 principle, 79–82, 149, 157
 Contour, crystal surfaces, 320
 Conventions in quartz nomenclature, 167–170
 Converse piezoelectric effect, 11
 Copper radiation, wavelengths of, 97, 100
 Corundum, 294
 Coupling, between modes of motion, 205, 221
 effect on shear and flexure, 224, 229
 flexure to shear, 224, 230
 l.f. shear to h.f. shear, 235
 minimized by rotation of cut, 219
 piezoelectric, 16, 45
 Cracks in quartz, 143, 161
 Crystal controlled oscillator—Definition, 358
 Crystal control, in receiver, 7
 Crystal—Function in oscillator, 356–359
 Crystal oscillator—Definition, 358
 Crystallographic axes, 101
 indices, 101, 182–183
 Crystolon, 295
 CT cuts—*see* Cuts
 mode of motion, 212
 thickness, 496
 Curie, Pierre and Jacques, 1, 11
 Current level, effect on filter stability, 456
 Cuts,
 X, 20, 24, 171
 Y, 24, 171
 Z, 24, 171
 AT, 6, 24
 AC, 26
 BT, 6, 24
 BC, 26
 CT, 6, 24, 412
 DT, 6, 24, 412
 ET, 6, 24
 FT, 6, 24
 GT, 6, 24, 28, 412
 MT, 24, 412
 NT, 24, 412
 +5° X-cut, 24, 33, 412, 538
 –18° X-cut, 24, 412
 +8.5°, 24
 Cuts parallel to the X axis, diagram, 107
 Cuts, orientation
 X, 24, 63, 69, 186
 Y, 24, 63, 69
 Z, 24, 63, 69, 179, 184, 195
 AT, 24–28, 63, 69, 137, 170, 182
 BT, 24–28, 63, 69, 130, 131, 137, 170, 182
 CT, 24, 28, 63, 69, 170, 182, 495
 DT, 24–28, 69, 170, 182, 495
 ET, 24
 FT, 24
 GT, 24–28, 63, 69, 170
 MT, 24, 31, 63, 69, 544
 NT, 24, 31, 63, 69, 132, 139, 548
 +5° X-cut, 24, 63, 69
 –18° X-cut, 24, 63, 69
 doughnut, 24
 +8.5°, 24
 harmonic, 24
 Cutting, fluids, 305
 into dice, 514, 515
 methods, 304
 plunge, 304
 speeds, 296
 traverse, 304
 Damping wire vibration, 430
 Davey, W. P., 98
 d, distance between atomic planes, 99
 Debye, P., 110
 Deposited electrode—advantages, 333
 Deposition of metal electrodes, 333, 420
 Design methods for plates, 205
 d'Heedene, A. R., 436
 Diamond, saw and sawing, 301–303, 504
 crushing, 302

- Diffraction of X-rays by crystals, 100
 Dimensioning, to isolate desired modes of motion, 241, 322
 AT cut, 246
 BT cut, 241, 324
 GT cut, 240
 related to crystal defects, 162
 Direct piezoelectric effect, discovery by Curies, 11
 Discoloration of platings, 336
 Divided coatings, 416, 421, 449
 Doerffler, H., 261
 Drews, W. F., 493
 D. spec. test set, 328
 DT cut—*see* Cuts
 thickness, 496
 mode of motion, 212
 Duplicator, 327
- Edge**, removing plating, 420, 521
 Efficiency of oscillators, 386
 —18° X-cut—*see* Cuts
 mode of motion, 212
 temperature coefficient, 24
 frequency constant, 440
 Egerton, L., 190
 Elastic constants
 by Atanasoff and Hart, 42
 by Mason, 45
 of rotated cuts, 50
 by Voigt, 40
 Elastic properties, 164
 Electric axes, 166, 170
 Electrical testing of twinned plates, 202, 203
 Electrode, connections, 417
 plated, 420, 497
 weight of, 344, 420
 Emery, abrasive, 295
 wheel, 290
 Equivalent circuit, of crystal, 21, 459
 derivation of, 46
 Error measurements in Laue photographs, 131
 see also orientation
 Espenschied, L. E., 15
 Etch figures, 167–200
 Etch figure instruments, 178, 190, 194, 195
 Etch pits, 169–178
 Etching, chemicals and process, 190–194
 factory process, 506–507
 to adjust frequency, 193–194
 to clean, 337
 to determine twinning and orientation, 164–203
 to stabilize frequency, 413, 446, 457
 ET cut—*see* Cuts, temperature coefficient
- Eutectic solder, 422
 Evacuation of crystal units, 434
 Evaporation of metals, 333
 Expansion, linear thermal, 164
 Extensional, vibration, 207
 equations, 217
- Facets**, etch pit, 169–183
 Fair, I. E., 6, 25, 59, 203, 279, 356, 395, 552
 Figure of Merit
 derivation of, 394–396
 equations for, 395, 459, 473
 measurement of, 409, 473
 purpose, 458–459
 relation to activity, 396–408
 Filters, electric, 8, 14, 414, 436
 Filter, for K_{β} radiation, 97, 98
 for monochromatic light, 149
 Filter crystal units, effect on performance
 with current level, 456
 divided coating, 449
 etching, 446
 humidity, dirt, etc., 454
 inductance variation, 437
 internal defects, 444
 linear dimension deviation, 441
 orientation deviation, 439
 resistance deviation, 438
 silver spotting, 448
 soldering supporting wires, 449
 wire resonances, 451
 Finish, on crystals, 319, 419
 Finished plates, effects of interior imperfections on, 160–163
 effects of twinning on, 194–203
 Firing of silver spots, 419, 520
 +5° X-cut—*see* Cuts, temperature coefficient, etc.
 flexure crystal, 541
 longitudinal properties, 547
 Flat lay cutting, 66–67
 Flatness, measuring, 307, 308
 Fattening laps, 308
 Flexural equations, 214, 542
 Flexural, +5° X-cut plate, 445, 541–543
 Flexural motions, 205
 Flexure and shear
 see Shear and Flexure
 Fluorescent screens, detection of X-rays, 97, 98
 Fluorine etching compounds, 190–193
 Fluxes for soldering, 424
 Fracture, 143, 161
 Frequency, accuracy in adjustment, 317
 adjustment in factory, 499
 adjustment of sealed crystal units, 432

- Frequency—*Cont.*
 modulated radio transmitter, 537
 of vibrations, 254–255, 258–261, 265, 266
 of rotated X-cut crystals, 43
 range of mfd. crystals, 499
- Frequency constant
 X-cut, 43, 440
 Y-cut, 26
 AT-cut, 26, 201
 AC-cut, 26
 BT-cut, 26, 201
 BC-cut, 26
 Y-cut rotated, 26
 +5° X-cut longitudinal, 440, 443, 540
 –18.5° X-cut, 440, 443
 +5° X-cut flexure, 445, 543
 with rotation about axes, 43, 219
 X-cut rotated about X-axis, 223, 440
- Frequency stability, coefficient of crystals, 390–393
 discovery of need, 4
 of oscillators, 375, 386–390, 396
- Frequency stabilization of crystal units, 434
- Frequency-temperature relation, second order derivative, 29
- FT cut—*see* Cuts, temperature coefficient, etc.
- FT-241 unit, 281, 403
- Gamma (γ)**, definition of, 105
- Garnet, 295
- Gas, effect on plating, 336
- Geiger-Müller counter for detection of X-rays, 98
- Glass housings, 432
- Glass sealing tool, 433
- Goss, F. A., 422
- Greenidge, R. M. C., 412
- Grinding, 290
 definition, 291
 to thickness, 513, 515
 effect on etch and cleavage figures, 179, 182, 185–189
 vs. lapping, 298
- Grinding machine
 Ultralap, 314
 Blanchard grinder, 315
- Grindstone, 291
- Grit size, 294
- GT cut—*see* Cuts, temperature coefficient, etc.
 flexure resonances, 239
 mode of motion, 212
- Handedness**, 103, 104, 166, 170, 185, 188
- Hardness, 298
- Hardness, of materials, 293
- Harmonic shear and flexure modes, 234
- Harrison, C. W., 410, 458
- Harrison, J. R., 442
- Hartley, R. V. L., 360
- Häüy, R. J., 99
- Haworth, F. E., 97
- Headed wire, mounting, 282
 for support, 425
 advantages, 427
 tool for making, 428
- Heater, for plating metals, 339, 341
- Heater, materials, in plating, 343
- Heegner, K., 380
- Heising, R. A., 1, 360, 380, 386
- Hight, S. C., 6, 27
- History, 1, 11
- h k l, definition, 102
- Holder, for grinding, 510, 512
- Holder, losses, 410, 472, 473, 485
 effect on activity, 409
 effect on P I Meter, 487
- Holder—*see* Mounting
- Hooked wire attachments, 425
- Hooke's Law, 250, 268
- Hot air blast soldering, 424, 498, 524
- Housing of crystal units, 431
- Humidity, effect on filter characteristics, 455
- Hydrofluoric acid etching, 190–194
- Immersion** fluids for quartz inspection, 90, 146, 150–152
- Impedance,
 circle diagram, 481
 of crystal, 479, 480
- Imperfections, interior, 140–163, 166
 effects on finished plates, 160–163, 194–203
- Inclusions, 144, 145, 159–161
- Index of refraction, 150–152, 164
- Indices, Miller, crystallographic, 101, 182–183
- Inductance constant of X-cut plates, 440, 444
- Input admittance of vacuum tube, 383–386
- Inspection for twinning, 164–203
 for interior imperfections, 140–163
- Inspectoscope, 145, 152, 502–503
- Insulation tests between electrode coatings, 421
- Interfering resonance, general, 33, 223, 226–229, 245, 323
 AT-cut, 234–236
 BT-cut, 235–238
- Interior defects and imperfections, 164–203
- Interplanar spacing, 99, 100, 103
- Ionization chamber for detection of X-rays, 97, 108

- I.R.E. crystal orientation angles, 62-63
standard conventions, 168, 170
- Jacobsen, L. S.**, 215
- Jensen, R. M.**, 446
- Kelvin's** model of quartz crystal, 12, 17
- Koga, I.**, 25, 56, 370-372, 377, 381
- Kohman, G. T.**, 90
- Lack, F. R.**, 6, 25, 59
- Lambda (λ)**, relation to theta (θ), 100
- Lambda (λ)**, definition, 99
- Lane, C. E.**, 416, 449
- Langevin, Paul**, 1, 12
- Lap**,
making flat, 308-310
materials, 296
wheel, 502
- Lapping**, 290, 295
definition, 291
edges, 515, 517
final adjustment, 319
nest, 312
precision, 305
process, speed, 299
squaring, 313
strokes, 309, 311
to size, nest lap, 514, 516
vs. grinding, 298
- Lapping machine**
Ultralap, 314
Blanchard grinder, 315
Hunt Hoffman, 315
improved, 316
- Lattice constants**, 103
- Laue**, 99
- Laue camera**, 129
- Laue photographs**, 128-135
- Lawson, A. W.**, 42
- Leak testing**, 529, 530
- Left-hand quartz**, 59, 166, 170, 185, 188
- Limiting frequency of oscillator**, 368, 369,
372, 377, 381, 382
- Linear thermal expansion**, 164
- Lippmann, G.**, 11
- Llewellyn, F. B.**, 370, 386
- Location of mass on mounting wire**, 287, 431
- Longitudinal vibrations**, 253-255
also see Modes of motion
- Low frequency quartz crystals**, 537
- Low temperature coefficient**, 6
also see Temperature coefficient
- Manufacturing**, education, 8
expansion, 8
- Manufacturing—Cont.**
operations, 500
- Mapping (conformal representation)**, 479
crystal impedance, 481
- Marrison, W. A.**, 6, 13
- Martin, D. K.**, 4
- Mason, W. P.**, 6, 11, 215, 287, 395, 412,
439, 537, 538, 543, 545, 552
- Matrix**,
of errors in orientation, 134, 135
- Matrix**,
for the plate edges P_1 , P_2 , P_3 on the
X, Y, Z coordinates, 115
- McSkimin, H. J.**, 208, 249
- Measurement**,
of circuit Q, 465
crystal voltage, 471, 477
Figure of Merit, 409
oscillator characteristics, 474, 477
Performance Index, 409, 461, 463
- Menke, H.**, 110
- Merit, Figure of**, 394-396, 409, 458-459,
473
- Metal electrodes**,
materials and processes, 333-334, 414-416
- Metal housings**, 432
- Meter, Performance Index**, 458
- Miller, J. M.**, 357, 358, 360
- Miller indices**, 101, 182, 183
- Modes of motion**
complex, 207
couplings, 23, 205, 219
equations, 214
—18.5° cut, 23
extensional, 23, 207, 217, 249, 253-259
+5° X-cut, 538
flexure, 205, 214, 249, 541-543
isolating desired motions, 240, 453
longitudinal, 23, 207, 217, 249, 253-
259
shear, 25, 209, 217, 230, 249, 259-264
standard cuts, 211
types of, 23
with rotation about axes, 219
X-cut rotated about X axis, 222
- Modes of vibration**
see Modes of motion
- Mohs scale of hardness**, 293
- Morrison, J. F.**, 33, 537
- Mounting**
air-gap type, 285
cages, 429
cantilever type, 278
clamping at corners, 285
clamp type, 5, 276
loss of activity, 409, 410

- Mounting—Cont.**
 pressure type, 5, 414
 principles, 276
 tank crystal, FT-241, 525, 526
 wire mounted unit, 498
 wire supported, 279, 415-417, 498
- MT cut—see** Cuts, temperature coefficient, etc.
 ratio of capacities, function of width to length ratio, 547
 frequency, function of width to length ratio, 547
 frequency vs. temperature, 549
- Needle** inclusions, 144, 145, 160, 161
- Nest**, lapping, 312, 516
- Nicolson, A. M.**, 1, 12, 356-358
- Nomenclature**, used in quartz, 167-170
- Non-linear crystals**, 469
- Normascope**, 79, 531
- NT cut—see** Cuts, temperature coefficient, etc.
 connection in oscillator, 551
 frequency as a function of width to length ratio, 550
 mode of motion, 212
 performance characteristics in special oscillator, 553
 unit, photograph, 553
 unit, station W2XOR, 554
- Optic axis**, 153-6, 166, 170
- Optical effect of etch-pits**, 173-178
- Optical properties**, 150-153, 164
- Optical orientation means**, 154, 155
- Optical twinning**, 143, 156, 166-169, 198, 202-203
- Oriascope**, 178-190, 506, 510, 531
- Orientation**
 choice of atomic planes, 116
 choice of method, 128, 164, 166
 effect on frequency, 201, 219
 electrical and optical rules for, 170
 by etch process, 164-190
 by Laue photography, 128-135
 by natural faces, 63-66, 95
 by optical means, 95, 155
 by X-rays, 95, 108-139
 prior to final plate check, 136-139
- Orthogonal axes**, 103
- Oscillator—Amplitude of oscillations**
 crystal grid-to-cathode, 367-368, 375, 376, 385
 crystal grid-to-plate, 367, 368, 378
 effect of crystal quality, 393, 396, 405, 406, 407
- Oscillator characteristics**, 474, 477
 correlation, PI measurement, 469
 crystal control, 1
 equivalent circuit, 458
- Oscillator circuits**
 arranged for PI purposes, 459
 Cady's, 357
 equivalent, 369, 379
 history, 356-358
 limiting frequency (f_0), 368-372, 377, 381-382
 Nicolson's, 15, 357
 NT flexure crystal, 551
 quality, 394
 quartz crystal, 13
 Rochelle salt, 13
- Oscillator circuit analysis**
 by complex functions, 369-379, 478
 conditions for oscillation, 361, 370, 379, 380, 383
 differential equations—general, 361
 differential equations—crystal grid-to-cathode, 363-365
 differential equations—crystal grid-to-plate, 362, 363
 differential equations—resistance load circuit, 365, 366
 filter theory application, 379, 380
 negative resistance concept, 382-386
 vector method, 380, 381
- Oscillator frequency—As function of**
 air-gap, 374
 amplification factor (μ), 374, 375
 capacitance, grid-to-cathode, 375
 capacitance, grid-to-plate, 374, 385
 capacitance, interelectrode, of tube, 367
 capacitance, paralleling crystal, 404, 405
 generated harmonics, 385
 plate circuit impedance, 365-369, 374, 375, 378, 385
 resistance, crystal, 367, 381
 resistance, grid lead, 369
 resistance, input of tube, 368
 resistance, oscillatory circuit, 368
 resistance, plate of tube, 374, 375
- Oscillator frequency—Equations for**
 crystal grid-to-cathode, 365, 371, 373, 404, 405
 crystal grid-to-plate, 363, 366, 377, 404, 405
- Oscillator harmonics—effect on frequency and amplitude**, 385

- Patents**, 1, 12, 14, 15, 23, 25, 410, 422
- Performance Index (PI)**
 change with crystal drive, 409
 definition, 398, 402, 461
 definition by equations, 460, 463
 derivation, 398-400
 effect of leakage resistance on, 410
 equations for, 399, 401, 402
 in crystal design, 407
 measurement of, 409, 470
 measurement theory, 461
 purpose, 460
 relation to activity, 405-407
- Performance Index meter**
 accuracy, 478
 analysis with crystals, 483
 calibration, 463, 464, 471
 circuital equations, 465-468
 circuits, 463
 conformal representation application, 479
 derivation of equations, 465, 490
 errors, 487, 489
 functional requirements, 462
 other uses, 472
 oscillator correlation, 469
 typical performance curves, 474, 477
 voltage generator, 469
- Phantoms**, 144, 157-159
- Pierce, G. W.**, 2, 13, 356, 365
- Piezoelectric**
 coefficients, 45, 164
 constant d_3 ; of a rotated length vibrating crystal, 546
 constants' relations, 39
 equation by Voigt, 34
 pile, 12
 theory, 17
- Pin-hole-oriroscope**, 184-190, 506-508
- Pirani gauge**, 348
- Pits, etch**, 169-178
- Plated crystal units**, 281, 412, 493
- Plating, division stylus**, 422
 equipment, 338
 machine, 345, 347
 method, 339
 operation, 353
 thickness, 338, 340, 344
 with silver, 520
- Polarized light, applied to crystals**, 70
 for inspection, 146
- Polarizers for inspection instruments**, 148
- Potter, R. K.**, 4
- Power output of oscillators**, 386
- Precision lapping**, 305
- Predimensioning—see Dimensioning**
- Pressure—air, for metal deposition**, 334
- Pressure type mountings**, 414
- Processing of quartz plates**, 413
- Protection of crystal plates**, 429
- Q, of crystal, definition**, 458
 observed, 23
- Q, of crystal, plus circuit**, 465
- Quality—definition**, 393
- Radio, telephone**, 3
- Ratio of capacitances of crystals**
 effect on Figure of Merit, 396
 effect on frequency stability, 392
 equation for, 45
 of flexure crystal, 544
 relation to electromechanical coupling, 45
 relation to oscillator frequency, 405
- Rayleigh, Lord**, 214
- Raw quartz imperfections, and inspection**, 140-163
- Raw quartz, orientation of**, 153-157, 183
- Receivers, use of crystal control**, 7
- Reflection oriascope**, 178, 531
- Refraction correction nomograph**, 92
- Refractive indices**, 150-152, 164
- Refractoscope**, 88, 151, 531
- Reich, H. J.**, 383
- Resistance, effective, of crystal**, 399, 401-404
- Resonance of supporting wires**, 430
- Resonant frequencies, theoretical**
 extensional modes, 254, 255, 258
 shear modes, 259, 260
 flexural modes, 261, 265, 266
- Resonator, quartz**, 2
- Right-hand quartz**, 58, 166, 170, 185, 188
- Rings, conoscope**, 155
- Ring eccentricity correction**, 84, 91-94
- River quartz**, 140, 153
- Rochelle salt**, 11, 12, 37, 50, 249
- Rotation about axes, effect on**,
 frequency and coupling, 219
 piezoelectric constants, 220
- Rotation of X-cut about X axis, effect on resonant frequency**, 223
- Rouge**, 295
- Sand blasting**, 183, 522
- Sawing**, 290
 definition, 291
 diamond, 301
 muck, 300
- Schramm, F. W.**, 243
- Sealing crystal units**, 432
- Sectioning**, 505, 506
- Shape, size, source of raw quartz**, 140

- Shear—*see* Modes of motion
 Shear, high frequency, 230
 Shear and flexure, 225
 resonances, 226, 227
 similarity of motions, 225
 Shear, theory, 19
 Shop, operations, 500
 Signal Corps, 8
 Silicon Carbide, 295
 Silver paste, 418
 Silver spots, 417–424
 Silver spot compressor, 518, 519
 Silver spotting, 448, 518
 Sizing abrasives, 294
 Slab cutting, 510, 511
 Smoky quartz, 141, 142
 Soldered connections, effect on unit characteristics, 450
 Soldering leads—Hot blast method, 424
 Soldering leads—Iron method, 424
 Soldering machine, 524, 525
 Soldering supporting wires, 498, 523–525
 Sorter, for blanks, 201–203, 534
 Sosman, R. B., 100
 Sowers, N. E., 390
 Speeds, of cutting, 296
 Spotting with silver, 417, 516, 518
 Spring suspension of crystal plates, 429
 Stability of sealed units, 432
 Stabilization of crystal units, 434
 Stauroscope, 533
 Stiffness—Compliance relation, 38
 Straight wire attachments, 424
 Straubel, J., 25
 Stress component equations, 253
 Stress—Strain equations for isotropic media, 268
 Structure, theory of, 99
 Submarine detecting devices, 12
 Support, by wires, 495
 Support wire soldering, 497
 Swickard, A. E., 493
 Sykes, R. A., 27, 204, 205, 276, 537
 Symmetry of quartz, 57
 Symmetry effect on piezoelectric constants, 20

Tank crystal, FT-241, 494
 Temperature coefficient,
 comparisons, 55, 201
 of elastic constants, evaluation, 53
 filter plates with deviations, 440
 from Voigt's relations, 49
 rotated cuts, general equations, 52
 X-cut, 32
 rotated X-cuts, equations, 545

 Temperature coefficient—*Cont.*
 +5° X-cut, 24, 545
 +5° X-cut, extensional, function W/l , 33, 540
 +5° X-cut, flexure, 445, 541–545
 +5° X-cut, flexure, analysis, 544
 –18.5° X-cut, longitudinal, 24, 443
 Y-cut, 27, 54
 Y-cut rotated, 27
 AC, 27
 AT, 6, 24, 27, 29, 54, 201
 BC, 27
 BT, 6, 24, 27, 29, 54, 201
 CT, 6, 24, 27, 29, 201
 DT, 6, 24, 27, 29, 201
 ET, 6
 FT, 6
 GT, 6, 29–32
 MT, 24
 NT, 24
 NT, ratio W/l , 549
 doughnut-shaped cut, 6, 24, 29
 long bar, 27, 32
 Terry, E. M., 358, 360, 363, 368
 Test methods for crystal activity, old and new, 460
 Test set for oscillator, 328
 Thermal fracture, 144
 Thermal properties of quartz, 164
 Theta (θ), Bragg angle, 99, 100, 105
 Thurston, G. M., 5, 243, 317, 393
 Tillyer, E. D., 25
 Time standards from quartz crystals, 13
 Titchmarch, E. C., 481
 Transducer, quartz crystal, 12
 Transformation, linear fractional, 479
 Transoceanic radio telephone, 3
 Transverse mode of vibration (*see shear also*) 259
 Twin and twinning, 143, 155–157, 166–169, 182, 196–200
 Brazil (optical), 143, 155–157, 166–169, 198
 combined, 198
 Dauphiné (electrical), 143, 166–169, 198
 effect on polarized light views, 156
 effect on etch figures, 167–169, 182
 effect on filter plates, 445, 451
 effect on finished plates, 202, 203
 in process, 419, 422, 448–451
 inspection for, 156, 167–169, 182, 202
 Twinoroscope, 180, 510, 512

Vacuum, for metal deposition, 334
 gauges, 348
 sealed units, 432

- Vacuum—*Cont.*
 sealing crystal units, 434
 tube development, 2
 valve, 351
- VanDyke, K. S., 15, 21, 358, 458
- Vapor pressures of metals, 335
- Veils, 145, 159–161
- Vertical cutting, 67–69
- Vibrations, normal modes
see also Modes of motion
 extensional
 long thin bar, 253
 thin rectangular plate, 254, 255
 flexural
 plate flexures, 260
 thickness flexures, 264
 shear, 259
- Vibration and shock protection, 429
- Vigoureux, P., 358, 368
- Voigt, piezoelectric equations, 1, 34, 40
- Wave** equations, mechanical vibration, 252
- WEAF, 4
- Wehe, H. G., 333
- Weight vs. thickness—platings, 344
- Weights, for controlling supporting wire vibrations, 431
- Weinhart, H. W., 333
- Western Electric Company, 2, 7, 8, 427, 430
- Wheeler, L. P., 368
- White radiation, 95, 96, 97
- Willard, G. W., 6, 25, 27, 45, 59, 88, 140, 164
- Willey, L. F., 441
- Wire attachment machines, 423, 426
- Wire mounted crystal unit, 493
- Wire mounting, wire resonance problems, 280, 283, 430, 451
- Wires, headed attachments, 422
 hooked, 425
 straight, 424
- Wire supported mounting, 279, 417
- Wright, J. W., 358
- Wyckoff, R. W. G., 103
- X** axis determination, 183–189, 508, 509
- X-cut—*see* Cuts, temperature coefficient, etc.
- X-rays, absorption of, 98
 angle between beam and plate (g), 99, 105, 110–114, 122–128
 Bragg law, Bragg angle of reflection (θ), 99, 100, 105
 characteristic radiation, 95, 96, 97
 detection of, 97, 98
 diffraction by crystals, 99–100
 filter for K_β radiation, 97, 98
 goniometry, 108–128, 536
 intensity of, factors governing, 95, 96, 97
 intensity of reflection from quartz, 105, 107, 108
 interlocking goniometer, 536
 method for orientation, 165
 “order” of reflected, 99, 100, 103
 physiological effects, 98
 production of, 95, 96
 protection, shielding materials, 98, 99
 spectrum, 96, 97
 target metal, choice of, 95, 96
 wavelength of, 95, 96, 97, 99, 100
 white radiation, 95, 96, 97
- Y-cut**—*see* Cuts, temperature coefficient, etc.
- Y-cut rotated, 26
- Young's modulus, 164, 250, 267
- Z-cut**—*see* Cuts
- Z section cutting, 67–69
 orientation, 179, 184
- Ziegler, A. W., 412, 425, 552